

SKU.1 CG-S 2x3A



SKU.1 CG-S 2x3A

- CG-S technology provides for automatic monitoring of up to 20 safety lights and emergency signs without requiring the transmission of additional data for each circuit
- Overload indicator
- Programmable switching for each individual light with no need to make adjustment directly to the light itself
- Automated isolation fault finding
- Assemblies use service-friendly module technology, wired ready for connection to triple-deck 4 mm² neutral terminals
- Wide finger-safe ventilation slits for optimum heat dissipation
- Simple, time-saving snap-on click installation on device rack
- Large sign rack for customized labeling
- Meets all EMV requirements for industrial and commercial use
- DEKRA system certification documents product quality and compliance with standards for the entire system
- Proof of function in DualGuard-S distributors of type ESF30 15-P and 30-P for 30 minutes in case of fire by means of a fire test of an independent material testing institute
- Conforms to RoHS and REACH

| | |
|-----------------------------------|------------------|
| Nominal AC voltage | 220-240V |
| Nominal DC voltage | 184-275V |
| Rated frequency | 50 or 60 Hz |
| Maximum head dissipation capacity | 4W |
| Outputs | |
| Rated current | 3A |
| short-circuit current | 1500A |
| Inrush current | 250A per circuit |

Order details

| Model | Included with delivery | Order no. |
|-------------------|--|-------------|
| SKU.1 CG-S 2 x 3A | Circuit switching 2 x 3A for component rack installation | 40071361560 |